



ZIP GUNS

Ideal for front end and heavy duty automotive work.

- Heat treated hardened steel barrel and piston for longer tool life.
- Built-in tease trigger for precise control.
- Standard quick change spring safety retainer.



2711-R
Zip Gun
(Short Hammer)



2715-R
Zip Gun
(Medium Hammer)

Specifications:

Model	Shank Size	Bore & Stroke	Impact Rate (bpm)	Aver. Air Consumption (cfm)	Length (in.)	Weight (lbs.)	Air Inlet (NPT)
2711-R	.401	3/4" x 2-5/8	3,200	4	6-3/4	3-1/2	1/4"
2715-R	.401	3/4" x 3-1/2	2,100	4	8-7/8	4-1/5	1/4"

Retainers & Steel



046094
.401 Shank Zip-Quick
Wire Retainer



046095
.401 Shank
Quick Change Wire Retainer
A047095
.498 Shank
Quick Change Wire Retainer



046096
.401 Shank
Beehive Wire Retainer
A047096
.498 Shank
Beehive Wire Retainer



102-
.401 Quick Change
Retainer
3200-3
.498 Quick Change
Retainer



Hammer Steel

Part#	Description	Shank Type	Length	
905	1-5/16" Wide Chisel	.401	6-1/4"	
955		.498	7"	
906	Bushing Splitter	.401	6-1/4"	
964		.498	7"	
909	Double Blade Panel Cutter	.401	6"	
959		.498	6-7/8"	
910T	3/4" Flat Chisel	.401	6-1/4"	
960T		.498	7"	
911	Tapered Punch	.401	6-1/2"	
961		.498	7"	
912T	5/8" Wide Side Cut Chisel	.401	5-3/4"	
962		.498	5-3/4"	
914	Spot Weld Breaker	.401	6-1/4"	
940	Moil Point	.401	7"	



Pneutool Parts & Service Co. Ltd.

33 Haas Road, Toronto, On M9W 3A1

Tel: 416-748-1200 Toll Free: 1-888-748-1201

Fax: 416-748-2695 E-mail: sales@pneutool.com

www.pneutool.com