




Accessories

Industrial



Filter Regulator Lubricators - FRL

Model	Width (A)	Length (B)
AFC-200H 1/4" 2 Piece FRL	88 mm / 3.36"	150 mm / 5.90"
BFC-200H 1/4" 2 Piece FRL	140 mm / 5.51"	206 mm / 8.11"
BFC-300H 3/8" 2 Piece FRL	140 mm / 5.51"	206 mm / 8.11"
CFC-400H 1/2" 2 Piece FRL	176 mm / 6.92"	250 mm / 9.54"
BC-300H 3/8" 3 Piece FRL	207 mm / 8.14"	172 mm / 6.77"
CC-400H 1/2" 3 Piece FRL	280 mm / 11.02"	195 mm / 7.67"



Maximm 160 psi on all models.

Regulator & Lubricators



9052
1/4" Brass
Regulator



301
In-line Oiler



1/4-Midget-Lube
1/4" Lubricator
9 cc Capacity



3/8-Midget-Lube
3/8" Lubricator
9 cc Capacity

1/4-Master-Lube
1/4" Lubricator
22 cc Capacity



3/8-Master-Lube
3/8" Lubricator
9 cc Capacity



360° Swivels

- 922A**
1/4" Swivel
- 933ST**
3/8" Swivel
- 944A**
1/2" Swivel



Self Storing Hose

- SS-1/4X20JT** - 1/4" x 20'
1/4" Swivel Fittings
- SS-1/4X25JT** - 1/4" x 25'
1/4" Swivel Fittings
- SS-3/8X25JT** - 3/8" x 25'
3/8" Swivel Fittings



High quality Poyurethane Self-Storing Hose. Complete with Pig Tails and Swivel Male NPT fittings at each end.

Construction



Heavy Duty Hose Barbs

- | | |
|---|---|
| 3502
1/4" Male Thread x 1/4" HB | 3510
3/8" Male Thread x 1/2" HB |
| 3506
3/8" Male Thread x 3/8" HB | 3511
3/4" Male Thread x 1/2" HB |
| 3509
1/4" Male Thread x 1/2" HB | 3512
1/2" Male Thread x 1/2" HB |



Hose Barb Swivels

- 9089**
3/8" NPT x 1/2" HB Swivel
Fits all Chipping Hammers or other tools with a 3/8" NPT Inlet Thread.
- 9090**
1/2" NPT x 1/2" HB Swivel
Fits all Diggers and Busters or other tools with a 1/2" NPT Inlet Thread.
- 9091**
7/8"-24 Thread x 1/2" HB Swivel
Fits all Chipping Hammers or other tools with a 7/8"-24 Inlet Thread.



Pneutool Parts & Service Co. Ltd.

33 Haas Road, Toronto, On. M9W 3A1
Tel: 416-7481200 Toll Free: 1-888-748-1201
Fax: 416-748-2695
E-mail: sales@pneutool.com www.pneutool.com

Construction Accessories

Construction Universal Couplers

UC-1/4M
1/4" Male Thread

UC-1/4F
1/4" Female Thread

UC-1/4H
1/4" Hose Barb

UC-3/8M
3/8" Male Thread

UC-3/8F
3/8" Female Thread

UC-3/8H
3/8" Hose Barb

UC-1/2M
1/2" Male Thread

UC-1/2F
1/2" Female Thread

UC-1/2H
1/2" Hose Barb

UC-3/4M
3/4" Male Thread

UC-3/4F
3/4" Female Thread

UC-3/4H
3/4" Hose Barb

UC-3WAY
3-Way Coupler

UCW-AWR-4
Replacement Washers



Construction Bowes Couplers

51522
3/8" Hose Shank-Male End

51532
3/8" Hose Shank-Female End

51542
3/8" Male Thread Male End

51552
3/8" Male Thread Female End

51524
1/2" Hose Shank-Male End

51534
1/2" Hose Shank-Female End

51544
1/2" Male Thread Male End

51554
1/2" Male Thread Female End

51526
3/4" Hose Shank-Male End

51536
3/4" Hose Shank-Female End

51546
3/4" Male Thread Male End

51556
3/4" Male Thread Female End



51562
3/8" Female Thread Male End

51572
3/8" Female Thread Female End

51564
1/2" Female Thread Male End

51574
1/2" Female Thread Female End

51566
3/4" Female Thread Male End

51576
3/4" Female Thread Female End



Construction Hose Whips

WHIP-1/2
Hose Whip 1/2" Swivel

WHIP-3/8
Hose Whip 3/8" Swivel

WHIP-7/8
Hose Whip 7/8-24" Swivel



Ensure long life and trouble free running with an AirPro Hose Whip. Fits all Chippers and Rivet Busters.

Construction Oilers

0L - Oiler
1/2" Port 3.8 oz capacity

1L - Oiler
3/4" Port 6.6 oz capacity

2L - Oiler
3/4" Port 9.9 oz capacity

3L - Oiler
1" Port 18.8 oz capacity

2A
Filler Cap



Optional Manual Relief replacement cap for the 0L, 1L, 2L and 3L Oilers.



Construction Heavy Duty Oilers

60-CF-M
Oiler 1-1/4" Port 1 Quart Capacity

230-CF-M
Oiler 2" Port 1 Gallon Capacity
Constant Feed



Construction Whip Check

1/8" Cable Two Eye



A must for all jobsites, the AirPro whip check prevents dangerous hose whipping when hoses become accidentally separated. Fits 3/8" to 1" Hose.

Construction Oiler Filter Combo & Inline Filters

OL-F - Oiler Filter Combo
1/2" Port 3.8 oz. Capacity

9074M
Inline Filter 1/2" Thread

9076M
Inline Filter 3/4" Thread



Super Heavy Duty Constant Feed Oiler, adjustable flow. Suitable for lubricating multiple tools. Place as close to the tools as is possible. Other sizes available.

Construction Accessories



Water Separators

.75ST

3/4" Ports -150 cfm

1ST

1" Ports -190 cfm

1.25ST

1-1/4" Ports -300 cfm

1.5ST

1-1/2" Ports -425 cfm

2ST

2" Ports - 770 cfm

2.5ST

2-1/2" Ports -1170 cfm

3ST

3" Ports -1750 cfm



Wright-Austin Water Separators remove 99% of entrained solids and water over 10 microns in size. These Heavy Duty Cast Iron Separators will provide years of trouble free service. All interior components are stainless steel, and an automatic drain is standard on all models.



Air Manifolds (ASME Certified)

ASME 2834BV

8 Station Manifold c/w Ball Valves

ASME 2834

8 Station Manifold



The *AirPro Air Manifold* offers a heavy duty, stackable design, rugged enough to withstand the toughest jobsite. All Air Manifolds comes with 2" NPT inlet and 3/4" NPT Outlets.



Air Movers

3VAMS 7.31"

3VAM 7.31" 8VAM 14.37"

6VAM 11.25" 10VAM 17"

AirPro Air Movers use small volume of high velocity compressed air passing through a series of small holes creating a venturi action, causing large volumes of low pressure air to be moved. (Steam pressure may also be used as a power source). Because air movers have no moving parts they are suited for use in venting air, dust, smoke and fumes in hazardous areas.



Air Tool Oil

High Quality Pneumatic Tool Lubricant, for indoor or outdoor summer use. Suitable for all Rotary Vane and Percussion Pneumatic tools. Available in **500ml, 1L and 4L**.



Anti-Freeze Oil

Good to -45° Celsius. Suitable for all Rotary Vane and Percussion Pneumatic Tools.

Available in **500ml, 1L and 4L**.



Electric Tool Steel

188 Shank - Fits Bosch - 11304, 11308, 12308, 12314, HSH10, HSH27, HSH28. Hitachi - H65, H85, H90SB. Kango - 2500

Tool#	Type	Width of Working End (in.)	Overall Length (in.)	Approx. Weight (lbs.)
1881520	Point	Std.	20	7-1/4
1882520	Chisel	Std.	20	7-1/4
1883500	Chisel	3	20	8
1886500	Asphalt Cutter	5	20	9



226 Shank - Fits Hitachi PH65A, H65SA, H65SB, Makita 8900N, 8900-S, HK1399, HM1300


Tool#	Type	Width of Working End (in.)	Overall Length (in.)	Approx. Weight (lbs.)
2261450	Point	Std.	18	-
2262450	Chisel	Std.	18	-
2263450	Chisel	2	18	-
2264410	Chisel	3	16	-
2269500	Asphalt Cutter	5	20	-



Electric Tool Steel


227 Shank - Fits Kango - 900, 900X, 928, 950, 950K, 950X, 1400. Hitachi - DH50SA, DH50SA1, H55SA, H55SC

Tool#	Type	Width of Working End (in.)	Overall Length (in.)	Approx. Weight (lbs.)
2271400	Moil Point	Std.	16	1-1/4
2272400	Chisel	Std.	16	1-1/4
2273400	Chisel	2	12	1
2274300	Chisel	3	12	1
P227B42	Clay Spade	4-1/2	18	5
P227B66K0500	Asphalt Cutter	5	18	5
P227B75K0300	Ground Rod Driver	3/4" opening	12	3




229 Shank - Fits Bosch - 11202, 11203, 11204, 11205, 11206, 11207. Kango - 420S, 501S 637S, 750S, 950KS, 950S, 950XS, 978S. Hitachi - DH38YE, DH40FA, DH50SB, H45SB and all tools that use the spline shank.

Tool#	Type	Width of Working End (in.)	Overall Length (in.)	Approx. Weight (lbs.)
2291450	Moil Point	Std.	18	1
2292450	Chisel	Std.	18	1
2293400	Chisel	2	12	1
2294350	Chisel	3	12	1
P229B42K05	Clay Spade	4-1/2	18	5



239 Shank - Fits all tools with SDS MAX Shank

Tool#	Type	Width of Working End (in.)	Overall Length (in.)	Approx. Weight (lbs.)
23901400	Moil Point	Std.	16	1-1/4
23902400	Chisel	Std.	16	1-1/4
23904400	Chisel	2	15	2
23907300	Chisel	3	12	2
P239B42K0500	Clay Spade	4-1/2	18	5
P239B45K0550	Pointed Clay Spade	5" Tapered	18	4-3/4
P239B66K0500	Asphalt Cutter	5	18	5
P239B77K0250	Ground Rod Driver	3/4" opening	12	1
23925220	SDS Max to SDS Plus Adaptor	-	7	1



Floor Cleaning Tools, Shanks and Bushing Tools

Tool#	Description
8979	Assembly with 5/64" (2mm) Thick Blade
8986	5/64" (2mm) Replacement Blade
32109	Nut & Bolt Set
9606	17" Kango Shank (227 Shank)
914754	12" Spline Shank (229 Shank)
914977	12" SDS Max Shank (239 Shank)
22715240	45mm Kango 1 pc Bushing Tool (227 Shank)
23920240	45mm SDS Max 1 pc Bushing Tool (239 Shank)



