



SG052B-17-Q Screwdriver

ARO SG052B-17-Q Positive Clutch Screwdrivers, are designed for rugged applications where driving torque may exceed final seating torque (as in wood and self-tapping applications). Because applied torque is controlled by the operator and can be limited by regulating airline pressure, these tools are recommended for wood or sheet metal fastening or for applications in metal or plastic that don't require precise torque.

Features -

- Skinsulate cushion grip.
- All steel body.
- Two stage throttle for control.
- All ball bearing for long life.



\$545.00

Special price while stock last.

Specifications:

Model	Free Speed (rpm)	Stall Torque		Length		Spindle Offset		Weight		Air Consumption		Sound Level dB(A)
		in.-lbs.	Nm	in.	mm	in.	mm	lbs.	kg.	cfm	L/s	
SG052B-17-Q	1,700	65	7.3	7.6	194	.8	21	2.6	1.2	25	12	78

Air Inlet - 1/4" NPTF

Air Pressure - 90 PSI

Hose Size - 5/16" (8mm)



PNEUTOOL Parts & Service Co. Ltd

33 Haas Road, Toronto, Ontario M9W 3A1 Tel: 416-748-1200

Toll Free: 1-888-748-1201 Fax: (416)-748-2695 E-mail: sales@pneutool.com



Ingersoll Rand

7804K 1/4" Dr. Drill-Driver Kit

The **IR 7804K Mini 1/4" Drill/Driver** delivers big power when your are in tight spaces. The hard driving five-vane motor delivers smooth and robust performance with double-sided, adjustable speed settings that provide variability for a broader range of applications. Double bearing construction ensures longer life, impressive balance, and reduced vibration.

Features -

- Composite housing with ergonomic textured grip provides user comfort with exceptional resistance to grease, chemicals, and extreme temperatures.
- Lightweight, pistol grip design with thumb actuated switch engineered for balance and one-handed operation.
- Variable speed trigger for maximum control.
- 22 piece drill bit and driver set.

\$169.50

**Special price
while stock last.**



Specifications:

Model	Drive (in.)	Max. Torque Reverse/Forward (ft. lbs.)	Free Speed (rpm)	Net Weight		Kit Weight		Overall Length		Sound dB(A) (Pressure/Power)
				lbs.	kg.	lbs.	kg.	in.	mm	
7804K	1/4	22.5	1,800	1.71	.78	2.7	1.22	7.25	191	83.6 / 94.6

Air Consumption - 1.92 cfm

@Load - 17.5 cfm

Air Inlet - 1/4" NPTF

Hose Size - 3/8"



PNEUTOOL Parts & Service Co. Ltd

33 Haas Road, Toronto, Ontario M9W 3A1 Tel: 416-748-1200

Toll Free: 1-888-748-1201 Fax: (416)-748-2695 E-mail: sales@pneutool.com