



Riveters

Rivnut Tools



- Metal housing.
- .5 hp motor and double reduction for exceptional power.
- Convenient double trigger for one hand direction change.
- Tease Throttle provides precise control.

Rivet Nut Sizes: M5, M6, 6-32, 8-32, 10-24, 10-32, 1/4-20

HN350B



- Lightweight and ergonomically designed.
- Double trigger for pull and reverse out of fastener, push to start forward to load Riv-Nut.
- Adjustable stroke c/w gauge for easy set up.
- Suspension bail for balancer use.
- Quick mandrel change.
- Bi-directional 360° rotation air hose universal joint inlet.
- Precise powerful air motor efficient for forward and reverse work.
- Rubber grip with soft touch for easy operation.
- Safety valve, automatically releases the excess pressure at 110 psi to protect the operator and tool.

Rivet Nut Sizes:

6-32, 8-32, 10-24, 10-32, 1/4-20, 5/16-18, 3/8-16, 1/2-13

CCP-25



Specifications:

Model	Speed (rpm)	Stroke (in)	Working Air Pressure (psi)	Average Air Consumption (cfm)	Traction Power (lbs.)	Weight (lbs.)	Air Inlet (NPT)
HN350B	350	N/A	90	5	-	2.8	1/4"
CCP-25	-	.276	85 - 95	4	4,800	5.3	1/4"



Pneutool Parts & Service Co. Ltd.

33 Haas Road, Toronto, On. M9W 3A1

Tel: 416-7481200 Toll Free: 1-888-748-1201

Fax: 416-748-2695

E-mail: sales@pneutool.com www.pneutool.com

Riveters

Blind Riveters

Ideal for duct work, aluminium, fibreglass, masonite, siding, automotive applications, light duty assembly applications and structural repairs. Maximum rating - mild steel.

810, 115 & 811C

- Quick release air valve.
- Exceptional pulling power for tough jobs.



810
3/16" Riveter



115
1/4" Riveter



811C
3/16" Riveter

CCP-240, CCP350 & CCP-4500

- Will pull stainless, monobolt and magna lok rivets. (Special nose piece may be required. Sold separately).
- Lightweight high impact polymer housing.
- Vacuum system, holds rivets in all positions.
- Full view mandrel collector.
- Front mounted swivel. (except CCP-4500)
- Shut-off valve.
- Ergonomic soft grip.



CCP-240
3/16" Riveter



CCP-350
1/4" Riveter



CCP-4500
5/16" Riveter

Specifications:

Model	Traction Power (lbs.)	Capacity (in.)	Air Pressure (psi)	Aver. Air Consumption (cfm)	Nose Pieces	Stroke (in.)	Weight (lbs.)	Air Inlet (NPT)	Hose Size (ID)
810	1,586	3/16	90	4	3/32", 1/8", 5/32", 3/16"	9/16	3-1/2	1/4"	3/8"
811C	1,983	3/16	90	4	3/32", 1/8", 5/32", 3/16"	11/16	3-3/10	1/4"	3/8"
115	2,380	1/4	90	4	1/8", 5/32", 3/16", 1/4"	10/16	4-1/8	1/4"	3/8"
CCP-240	2,400	3/16	85 - 90	4	3/32", 1/8", 5/32", 3/16"	49/64	4-1/3	1/4"	3/8"
CCP-350	3,700	1/4	85 - 90	4	3/16", 7/32", 1/4"	19/32	4-3/5	1/4"	3/8"
CCP-4500	4,500	5/16	85 - 90	4	3/16", 7/32", 1/4", 5/16"	.984	4-5/8	1/4"	3/8"